

APPLICATION RATES AND TIMING

Apples:	4 x 5L/ha + 3 x 10L/ha. (Minimum program.) Commence at petal fall, and continue at 10-14 day intervals. Adjust timing so that final application occurs 7-10 days prior to harvest. Water rate 1,000L/ha
Brassicas:	2-3 x 5L/ha. At heading stage or severe weather change. Water rates 200-300L/ha
Carrots:	2-3 x 5L/ha. When sufficient leaf cover to intercept spray, then at 7-10 day intervals. Water rate 200-300L/ha
Kiwifruit/Pawpaw:	4 x 5L/ha. Commence at fruitlet stage and continue at 10-14 day intervals. Use with Rutec CaP is recommended. Water rate 1,000L/ha
Lettuce:	2-3 x 5L/ha. At 10-14 days after transplanting or emergence, then at 7-10 day intervals. Depending on severity of deficiency. Water rate 200L/ha minimum.
Pears:	4 x 5L/ha + 2 x 10L/ha. Timing and application as for apples.
Peppers / Capsicum:	2-3 x 5L/ha. Commence prior to flowering and continue at 7-10 day intervals. Water rate 300L/ha
Rockmelons/ Watermelons:	3 x 5L/ha. Commence immediately after flowering then at 7-10 day intervals. Water rate 200-300L/ha
Stone fruits:	4 x 10L/ha or 2 x 5L/ha + 3 x 10L/ha. Timing and application as for apples.
Strawberries:	5L/ha per spray. From flowering onwards every 10-14 days. Use with Rutec CaP is recommended. Water rate 1,000L/ha
Tomatoes:	2-4 x 5L/ha. From flowering on second truss, at 7-10 day intervals. Use with Rutec CaP is recommended. Water rate 300L/ha minimum.
Post Harvest Dip:	600ml per 100litres water for Golden Delicious & sensitive varieties. 1.25 litres per 100litres water for other varieties

KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING



DIPFOL Ca

ANALYSIS

CALCIUM (Ca) as calcium chloride

%W/W

16.0

g/L

160.0

This product contains:

Water
Solids

66.9%w/w

33.1%w/w

20L

200L

1000L

Manufactured by

RUTEC PTY LTD

23 HARGRAVE STREET
TAMWORTH NSW 2340

GENERAL INSTRUCTIONS

MIXING AND SPRAYING

Shake the container thoroughly before use. Pour through the filter into the tank three quarters filled with water, whilst agitating. Top up with water and continue to agitate until spraying is completed.

COMPATIBILITY

RUTEC Dipfol Ca is compatible with many agrichemicals. Contact your distributor for information.

STORAGE AND DISPOSAL

Store in the closed original container, in a well-ventilated area as cool as possible. Protect from frost. Do not store for prolonged periods in direct sunlight. Triple rinse containers before disposal and add hoses to tank mix or dispose of rinsate in a disposal pit away from desirable plants, their roots and watercourses. On-site disposal of undiluted chemicals is unacceptable. Destroy empty containers by breaking, crushing or puncturing them. Dispose of the containers at a local authority landfill that does not burn its refuse. If there is no local authority landfill readily available in your area, bury the containers to a depth of 500mm or more at a licenced/approved disposal site. In some states wastes can only be buried at a licenced landfill. Do not burn empty containers or product.

SPILLAGE

Hose small spillage (less than 1 litre of concentrate) away with a large excess of water. Large spillage should not be directed to drains. Large spillage should be absorbed in sawdust or sand and the absorbent material containing the product disposed of in a sealed container at an approved disposal site.

PROTECTION OF WILDLIFE, FISH, CRUSTACEA AND ENVIRONMENT

Do NOT contaminate streams, rivers or waterways with the chemical or used containers.

SAFETY DIRECTIONS

Harmful if swallowed. Avoid contact with eyes, skin and clothing. Wash thoroughly with soap and water after handling. Avoid inhaling spray mist.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre Ph: 13 11 26. If in eyes, flush with water for 15 minutes and see a doctor.

EXCLUSION OF WARRANTIES AND LIMITATIONS OF LIABILITY

The purchaser acknowledges that no express or implied warranty, condition, description or representation is given or made by Rutec Pty Ltd (ABN 91 002 846 988) in relation to this product. To the maximum extent permitted by the law, all warranties, terms, conditions and any duty of care which would otherwise be implied or arise by operation of law, statute or use in relation to this product are hereby excluded as against any and all persons, whether purchasers of this product or not.

To the maximum extent permitted by law, Rutec's total liability to any person in connection with this product, whether arising from a breach of any express or implied term, condition or warranty, any duty of care or otherwise, other than any liability which by these terms or otherwise is excluded, shall not exceed the amount paid by the purchaser to the vendor for this product, whether or not such liability results from or involves negligence on the part of Rutec.