RUTEC liquid chelated Manganese is a foliar or soil applied micronutrient and is non-phytotoxic when used as directed. It is completely available and absorbed by the leaf surface or the root system because of the natural complexing properties of its EDTA chelating complex.

APPLICATION RATES AND TIMING

| CROP | RATE L/ha | TIMING | WATER L/ha |
|---|--------------|---|---------------|
| All beans | 1-2 | Apply when plants are at 4 leaf stage. | 500 |
| Potatoes | 1-2 | Apply at 2-3 weeks after emergence. | 500 |
| Brassicae, Celery,Lettuce, Carrots | 1-2 | Apply 6-10 days after transplanting, 10-14 days after emergence if seed- ed crop.Repeat as required | 500 |
| Cucurbits, Melons, Cucumbers | 1-2 | Apply prior to flowering | 500 |
| Tomatoes | 2-3 | Apply 6-10 days after transplanting. Repeat as required. | 500 |
| Barley,oats, lucerne,wheat sorghum, | 2-3 | Apply when plants are young as this is a criticsl time. Repeat as required | 500 |
| Citrus, | 2.5-4.5 | Apply 2 weeks after bloom.Repeat as | 500 |
| Stone fruits, Pome fruits | 1-2.5 | required Apply 2 weeks after bloomRepeat as required | 500 |
| Strawberries and all berries | 1-2.5 | Apply 5-7 days afetr transplanting. | 500 |
| Ornamentals and flowers | 1.2-2.5 | Apply every month | 500 |
| Pastures | 1-2.5 | Apply to pasture when Manganese deficiency occurs | 500 |
| Lawn and Turf | 50ml/sq.m | Apply monthly | 500 |
| | | | |

KEEP OUT OF REACH OF CHILDREN READ SAFETY DIRECTIONS BEFORE OPENING



MANGANESE

| Α | NALYSIS | | %W/V |
|----|--------------------------------|-----------------|--------------|
| М | ANGANESE (Mn)) as an EDT | A complex | 6.0 |
| W | etters, stickers and dispersan | ts | 1.0 |
| TI | nis product contains | Solids Water | 54.4 65.6 |

20L 200L 1000L

Manufactured by
RUTEC PTY LTD

23 HARGRAVE STREET TAMWORTH NSW 2340

GENERAL INSTRUCTIONS MIXING AND SPRAYING

Shake the container thoroughly before use. Pour through the filter into the tank three quarters filled with water, whilst agitating. Top up with water and continue to agitate until spraying is completed. PRECAUTIONS

Avoid application under extremes of climate eg. Rapid drying conditions, extremely slow drying conditions, frost rain or when frost or rain are anticvipated COMPATIBILITY

RUTEC products are widely compatible with many agrichemicals. Contact your distributor for information. STORAGE AND DISPOSAL

Store in the closed original container, in a well-ventilated area as cool as possible. Protect from frost. Do not store for prolonged periods in direct sunlight.

Triple rinse containers before disposal and add hosings to tank mix or dispose of rinsate in a disposal pit away from desirable plants, their roots and watercourses.

On-site disposal of undiluted chemicals is unacceptable. Destroy empty containers by breaking, crushing or puncturing them. Dispose of the containers at a local authority land fill that does not burn its refuse. If there is no local authority landfill readily available in your area, bury the containers to a depth of 500mm or more at a licenced/approved disposal site. In some states wastes can only be buried at a licenced landfill. Do not burn empty containers or product. SPILLAGE

g/L Hose small spillage (less than 1 litre of concentrate) away with a large excess of water. Large spillage should not be directed to drains. Large spillage should be absorbed in saw-600 dust or sand and the absorbent material containing the prod-

60 dust or sand and the absorbent material containing the product disposed of in a sealed container at an approved disposal site.

PROTECTION OF WILDLIFE, FISH, CRUSTACEA AND ENVIRONMENT

Do NOT contaminate streams, rivers or waterways with the chemical or used containers.

SAFETY DIRECTIONS

Harmful if swallowed. Avoid contact with eyes, skin and clothing. Wash thoroughly with soap and water after handling. Avoid inhaling spray mist. **FIRST AID**

If poisoning occurs, contact a doctor or Poisons Information Centre Ph: 13 11 26. If in eyes, flush with water for 15 minutes and see a doctor.

EXCLUSION OF WARRANTIES AND LIMITATIONS OF LIABILITY The purchaser acknowledges that no express or implied warranty, condition, description or representation is

Implied warranty, condition, description or representation is given or made by Rutec Pty Ltd (ABN 91 002 846 988) in relation to this product. To the maximum extent permitted by the law, all warranties, terms, conditions and any duty of care which would otherwise be implied or arise by operation of law, statute or use in relation to this product are hereby excluded as against any and all persons, whether purchasers of this product or not. To the maximum extent permitted by law, Rutec's total liability to any person in connection with this product, whether arising from a breach of any express or implied term, condition or warranty, any duty of care or otherwise is excluded, shall not exceed the amount paid by the purchaser to the vendor for this product, whether or not such liability results from or involves negligence on the part of Rutec.